证 明 CERTIFICATE 021.00716

## 本证明之附件是向中国专利局作为受理局提交的下列国际申请副本

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY OF THE BELOW IDENTIFIED INTERNATIONAL APPLICATION THAT WAS FILED WITH THE CHINESE PATENT OFFICE AS RECEIVING OFFICE

国际申请号:

PCT/CN02/00826

INTERNATIONAL APPLICATION NUMBER

国际申请日:

19 NOV 2002 (19.11.02)

INTERNATILNAL FILING DATE

发明名称:

Method and Apparatus for Connecting a Micro-Actuator

TITLE OF INVENTION

to Driver Arm Suspension

申 请 人:

SAE MAGNETICS (H. K. ) LTD.

APPLICANT

中华人民共和国国家知识产权局局长
COMMISSIONER OF THE STATE INTELLECTUAL PROPERTY
OFFECE OF THE PEOPLE'S REPUBLIC OF CHINA

五季川

二零零二年十二月三十日 DECEMBER. 30. 2002



## PCT

#### REQUEST

The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty.

For receiving Office use only	-
International Application No. PCT/CN 02/ 00 824	
International Filing Date 9 NOV 2002 (1 9. 1 1. 02	)
RO/CN 中华人民共和国国家知识产权局 PCT international Application	
Name of receiving Office and "PCT International Application"	

according to the Patent Cooperation Treaty. Applicant's or agent's file reference (if desired) (12 characters maximum) FPEL02150037 TITLE OF INVENTION Box No. I Method and Apparatus for Connecting a Micro-Actuator to Driver Arm Suspension APPLICANT This person is also inventor Box No. II Name and address: (Family name followed by given name; for a legal entity, full official designation. Telephone No. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.) Facsimile No. SAE MAGNETICS (H. K. ) LTD. SAE Tower, Teleprinter No. 38-42 Kwai Fung Crescent Kwai Chung N. T. Applicant's registration No. with the Office Hong Kong Special Administrative Region, P. R. of China State (that is, country) of nationality: State (that is, country) of residence: CN CN the States indicated in the Supplemental Box This person is applicant all designated States all designated States except the United States of America the United States of America only for the purposes of: FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR(S) Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.) This person is: applicant only YAO, Minggao Winnerway Industrial Area, applicant and inventor Nancheng, Dongguan City inventor only (If this check-box is marked, do not fill in below.) Guangdong Province, Applicant's registration No. with the Office P. R. of China Zip Code: 511700 State (that is, country) of residence: State (that is, country) of nationality: This person is applicant all designated all designated States except the United States of America the United States the States indicated in the Supplemental Box for the purposes of: of America only Further applicants and/or (further) inventors are indicated on a continuation sheet. AGENT OR COMMON REPRESENTATIVE; OR ADDRESS FOR CORRESPONDENCE The person identified below is hereby/has been appointed to act on behalf common agent representative of the applicant(s) before the competent International Authorities as: Name and address: (Family name followed by given name; for a legal entity, full official designation. Telephone No. The address must include postal code and name of country.) (852)28284688 China Patent Agent (H.K.) Ltd. Facsimile No. 22/F, Great Eagle Centre (852)28271018 23 Harbour Road, Wanchai Teleprinter No. Hong Kong Special Administrative Region The People's Republic of China Agent's registration No. with the Office Address for correspondence: Mark this check-box where no agent or common representative is/has been appointed and the space above is used instead to indicate a special address to which correspondence should be sent.



Sheet No. ...2...

Continuation of Box No.	III FURTHER	APPLICANT(S) A	ND/OR (FUR)	ΓHER)	INVENTOR(S)		
If none of the following sub-boxes is used, this sheet should not be included in the request.							
Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)  SHIRAISHI Masashi Flat C, 22/F, Tower 9  Laguna Varde (Phase II A)  Hung Hom, Kowloon  Hong Kong Special Administrative Region P. R. of China  State (that is, country) of nationality:  State (that is, country)  This person is applicant all designated all designated States except					This person is:  applicant only applicant and inventor inventor only (If this check-hox is marked, do not fill in below.)  Applicant's registration No. with the Office  of residence:  the United States of America only the States indicated in the Supplemental Box		
for the purposes of:	States		ates of America		The Supplemental Dox		
Name and address: (Family The address must include posta Box is the applicant's State (tha	l code and name of cour	itry. The country of th	e address indicated	d in this	This person is:  applicant only  applicant and inventor  inventor only (If this check-hox is marked, do not fill in below.)  Applicant's registration No. with the Office		
State (that is, country) of na	tionality:		State (that is, e	country	of residence:		
This person is applicant for the purposes of:	all designated States	all designated the United St	States except ates of America		the United States of America only the States indicated in the Supplemental Box		
Name and address: (Family The address must include posta Box is the applicant's State (tha	l code and name of cou	itry. The country of th	e address indicated	d in this	This person is:  applicant only  applicant and inventor  inventor only (If this check-box is marked, do not fill in helow.)  Applicant's registration No. with the Office		
State (that is, country) of nationality:  State (that is, country)				country	) of residence:		
This person is applicant for the purposes of:	all designated States	all designated the United St	States except ates of America		the United States of America only the States indicated in the Supplemental Box		
Name and address: (Family The address must include posta Box is the applicant's State (tha	il code and name of cou	ntry. The country of th	e address indicated	d in this	This person is:  applicant only  applicant and inventor  inventor only (If this check-box is marked, do not fill in below.)  Applicant's registration No. with the Office		
State (that is, country) of na	ationality:	· · · · · · · · · · · · · · · · · · ·	State (that is, c	ountry)	of residence:		
This person is applicant for the purposes of:	all designated States	all designated the United Sta	States except ites of America		the United States of America only the States indicated in the Supplemental Box		
Further applicants and/or (further) inventors are indicated on another continuation sheet.							

### Sheet No. ...3...

Box No.	V DESIGNATION OF STATES	Mark the ap	plicable check-boxes below;	at leas	t one must he marked.	
The following designations are hereby made under Rule 4.9(a):						
Region	al Patent					
Regional Patent  AP ARIPO Patent: GH Ghana, GM Gambia, KE Kenya, LS Lesotho, MW Malawi, MZ Mozambique, SD Sudan, SL Sierra Leone, SZ Swaziland, TZ United Republic of Tanzania, UG Uganda, ZM Zambia, ZW Zimbabwe, and any other State which is a Contracting State of the Harare Protocol and of the PCT (if other kind of protection or treatment desired, specify on dotted line)						
□ EA	A Eurasian Patent: AM Armenia, AZ Azerbaijan, BY Belarus, KG Kyrgyzstan, KZ Kazakhstan, MD Republic of Moldova, RU Russian Federation, TJ Tajikistan, TM Turkmenistan, and any other State which is a Contracting State of the Eurasian Patent Convention and of the PCT					
□ EP						
□ OA						
Nation	al Patent (if other kind of protection	treatment desir	ed, specify on dotted line):			
	United Arab Emirates	GM Gambia			New Zealand	
	Antigua and Barbuda	HR Croatia			1 Oman	
	Albania	HU Hungary		□ РН	Philippines	
Пам	Armenia	ID Indonesia	1	$\square$ PL	Poland	
□ AT	Austria	IL Israel		☐ PT	Portugal	
□ ATI	Australia	IN India		□ RC	Romania	
	Azerbaijan	IS Iceland		□ RU	Russian Federation	
□ RA	Bosnia and Herzegovina	.IP Janan				
	Barbados	KF Kenya		$\square$ sp	Sudan	
	Bulgaria	KG Kyroyzsi	an	□ SE	Sweden	
	Brazil	KP Democra	tic People's Republic	$\Box$ sc	Singanore	
	Belarus	of Vores	de l'eopie s'Republic		Slovenia	
□ BX	Belize	VD Danublia	of Vorce		Slovelia	
		KK Kepublic	of Rolea		Sierra Leone	
	Canada				Tajikistan	
	& LI Switzerland and Liechtenstein				1 Turkmenistan	
	China		a		T Turkmenistan	
	Colombia	LR Liberia				
	Costa Rica				Turkey	
□ cu	Cuba	LT Lithuani		L TI	Trinidad and Tobago	
☐ CZ	Czech Republic	LU Luxemb	ourg			
	Germany				United Republic of Tanzania	
□ DK	Denmark	MA Morocco			Ukraine	
	Dominica	MD Republic	of Moldova		Uganda	
	Algeria				United States of America	
☐ EC	Ecuador	MG Madagas	car			
□ EE	Estonia	MK The form	ner Yugoslav Republic of	∐ UZ	Uzbekistan	
	Spain				Viet Nam	
□ FI	Finland	MN Mongoli			J Yugoslavia	
□GB	United Kingdom				South Africa	
□ cn	Grenada	MX Mexico		$\square$ zn	1 Zambia	
☐ GE	Georgia	MZ Mozamb	ique	$\square$ zv	V Zimbabwe	
	Ghana					
					541:-14	
Check-l	boxes below reserved for designating	ites which have	become party to the PCT a	iter iss	uance of this sneet:	
│ □		_		_		
other de exclude any des	tionary Designation Statement: In esignations which would be permitte d from the scope of this statement. The ignation which is not confirmed before that the expiration of that time limit.	nder the PCT opplicant declar be expiration o	except any designation(s) in es that those additional design f 15 months from the priorit	ndicate gnation y date i	d in the Supplemental Box as being s are subject to confirmation and that	

Sheet No. ...4...

Box No. VI PRIORITY	CLAIM							
The priority of the followin	g earlier application(s) is here	by claimed:		A				
Filing date	Number	V	Where earlier application is:					
of earlier application (day/month/year)	of earlier application	national application: country or Member of WTO	regional application:* regional Office	international application: receiving Office				
item (1)								
item (2)								
item (3)								
item (4)								
item (5)	·							
Further priority claims	are indicated in the Suppleme	ntal Box.		·				
if the earlier application was above as:	ested to prepare and transmit filed with the Office which for	the purposes of this internat	tional application is the r	arlier application(s) (only ecciving Office) identified				
* Where the earlier applicati		item (3) item (		Supplemental Box				
Industrial Property or one M	on is an ARIPO application, in Tember of the World Trade Or	ganization for which that e	party to the Parts Conve arlier application was file	ed (Rule 4.10(b)(ii)):				
Box No. VII INTERNAT	TIONAL SEARCHING AUT	THORITY		• • • • • • • • • • • • • • • • • • • •				
Choice of International Sei	arching Authority (ISA) (if to	vo or more International Se -letter code may be used):	earching Authorities are o	competent to carry out the				
ISA /								
Request to use results of ea International Searching Auth	rlier search; reference to the	nat search (if an earlier sec	arch has been carried out	t by or requested from the				
Date (day/month/year)	Numbe	er Count.	ry (or regional Office)					
Box No. VIII DECLARAT	TIONS	•						
The following declarations check-hoxes below and indica	are contained in Boxes Nos. ' ate in the right column the num	VIII (i) to (v) (mark the ap her of each type of declarat	plicable tion):	Number of declarations				
Box No. VIII (i)	Declaration as to the identity	of the inventor		·:				
Box No. VIII (ii)	Declaration as to the applicate, to apply for and be gra							
Box No. VIII (iii)	Declaration as to the applicant's entitlement, as at the international filing date, to claim the priority of the earlier application							
Box No. VIII (iv)	Declaration of inventorship United States of America)	(only for the purposes of t	the designation of the	:				
Box No. VIII (v)	Declaration as to non-prejuc	dicial disclosures or except	tions to lack of novelty	:				

Sheet No. . . . 5

	Sheet No	
Box No. 1X CHECK LIST; LANGUAGE O	OF FILING	
This international application contains:  (a) the following number of sheets in paper form:	This international application is accompanied by the following item(s) (mark the applicable check-boxes below and indicate in right column the number of each item):	Number of items
request (including	1. Kan fee calculation sheet	:
declaration sheets) : 5	2. Z original separate power of attorney	:
description (excluding sequence listing part) : 6	3.  original general power of attorney	:
claims : 6	4. copy of general power of attorney; reference number, if any:	•
abstract : 1		
drawings : 7	5. statement explaining lack of signature	•
Sub-total number of sheets: 25	6. priority document(s) identified in Box No. VI as item(s):	:
sequence listing part of description (actual number of sheets if filed in paper	7. translation of international application into (language):	:
form, whether or not also filed in computer readable	8. separate indications concerning deposited microorganism or other biological material	:
form; see (b) below) : 25	9. sequence listing in computer readable form (indicate also type and number of carriers (diskette, CD-ROM, CD-R or other))	
(b) sequence listing part of description filed in computer readable form	(i) copy submitted for the purposes of international search under Rule 13ter only (and not as part of the	
(i) only (under Section 801(a)(i))	international application)	:
(ii) in addition to being filed in paper form (under Section 801(a)(ii))	(ii) (only where check-box (b)(i) or (b)(ii) is marked in left column) additional copies including, where applicable, the copy for the purposes of international search under	
Type and number of carriers (diskette, CD-ROM, CD-R or other) on which the sequence listing part is contained (additional copies to be indicated under item 9(ii), in	Rule 13 <i>ter</i> (iii) together with relevant statement as to the identity of the copy or copies with the sequence listing part mentioned in left column	:
right column):	10.  other (specify):	:
ruin state despite as which	Language of filing of the	
Figure of the drawings which should accompany the abstract:	international application: EN	
	T, AGENT OR COMMON REPRESENTATIVE uning and the capacity in which the person signs (if such capacity is not obvious from read	ing the request
	TANTON CONTRACTOR (HONG)	
<del></del>	For receiving Office use only	
Date of actual receipt of the purported international application:	1 9 NOV 2002 (1 9 1 1 0 2)	rawings: received:
<ol> <li>Corrected date of actual receipt due to later timely received papers or drawings complet the purported international application:</li> </ol>	but	
4. Date of timely receipt of the required corrections under PCT Article 11(2):		not received:
5. International Searching Authority (if two or more are competent): ISA /	6. Transmittal of search copy delayed until search fee is paid	
	For International Bureau use only	
Date of receipt of the record copy by the International Bureau:		
§		

This sheet is not part of and does not count as a sheet of the international application.

#### For receiving Office use only FEE CALCULATION SHEET Annex to the Request (19.11.02) 9 [[ 2002 Applicant's or agent's file reference Date stamp of the receiving Office Applicant CALCULATION OF PRESCRIBED FEES **CNY500** T 1. TRANSMITTAL FEE . . . . CNY1500 S COO. SEARCH FEE . International search to be carried out by (If two or more International Searching Authorities are competent to carry out the international search, indicate the name of the Authority which is chosen to carry out the international search.) 3. INTERNATIONAL FEE **Basic Fee** Where item (b) of Box No. IX applies, enter Sub-total number of sheets 25 Where item (b) of Box No. IX does not apply, enter Total number of sheets CHF 650: ъ1 b1 first 30 sheets . b2 number of sheets fee ner sheet in excess of 30 additional component (only if sequence listing part of description is filed in computer readable form under Section 801(a)(i), or both in that form and on paper, under Section 801(a)(ii)): ъ3 fee per sheet В CHF650 Add amounts entered at b1, b2 and b3 and enter total at B. Designation Fees The international application contains \_\_\_\_1 \_\_ designations. D **CHF140 CHF140** number of designation fees amount of designation fee payable (maximum 5) **CHF790** Π Add amounts entered at B and D and enter total at I . . . . (Applicants from certain States are entitled to a reduction of 75% of the international fee. Where the applicant is (or all applicants are) so entitled, the total to be entered at I is 25% of the sum of the amounts entered at B and D.) P FEE FOR PRIORITY DOCUMENT (if applicable) CNY2000CHF790 TOTAL Add amounts entered at T, S, I and P, and enter total in the TOTAL box The designation fees are not paid at this time. MODE OF PAYMENT authorization to charge deposit account (see below) postal money order cash coupons revenue stamps cheque \_\_\_ bank draft other (specify): AUTHORIZATION TO CHARGE (OR CREDIT) DEPOSIT ACCOUNT Receiving Office (This mode of payment may not be available at all receiving Offices) Deposit A Authorization to charge the total fees indicated above. Date: (This check-box may be marked only if the conditions for deposit accounts of the receiving Office so permit) Authorization to charge any deficiency or credit any overpayment in the total fees indicated above. Name: Authorization to charge the fee for priority document. Signature:

20

25

30

# METHOD AND APPARATUS FOR CONNECTING A MICRO-ACTUATOR TO DRIVER ARM SUSPENSION

#### **Background Information**

The present invention relates to magnetic hard disk drives. More specifically, the present invention relates to a method of connecting the micro-actuator to the driver arm suspension.

In the art today, different methods are utilized to improve recording density of hard disk drives. Figure 1 provides an illustration of a typical drive arm configured to read from and write to a magnetic hard disk. Typically, voice-coil motors (VCM) 102 are used for controlling a hard drive's arm 104 motion across a magnetic hard disk 106. Because of the inherent tolerance (dynamic play) that exists in the placement of a recording head 108 by a VCM 102 alone, micro-actuators 110 are now being utilized to 'fine-tune' head 108 placement. A VCM 102 is utilized for course adjustment and the micro-actuator then corrects the placement on a much smaller scale to compensate for the VCM's 102 (with the arm 104) tolerance. This enables a smaller recordable track width, increasing the 'tracks per inch' (TPI) value of the hard drive (increased drive density).

[0003] Figure 2 provides an illustration of a micro-actuator as used in the art. Typically, a slider 202 (containing a read/write magnetic head; not shown) is utilized for maintaining a prescribed flying height above the disk surface 106 (See Figure 1). Micro-actuators may have flexible beams 204 connecting a support device 206 to a slider containment unit 208 enabling slider 202 motion independent of the drive arm 104 (See Figure 1). An electromagnetic assembly or an electromagnetic / ferromagnetic assembly (not shown) may be utilized to provide minute adjustments in orientation/location of the slider/head 202 with respect to the arm 104 (See Figure 1).

[0004] The physical and electrical coupling of a hard disk micro-actuator and magnetic head to a drive arm suspension can be difficult due to the environment within which it must operate. Using silver paste (high mercury-content epoxy) for physical/electrical attachment has drawbacks due to the viscous nature of epoxy under changing temperature and humidity. Under certain temperature and humidity conditions, the epoxy can deform, affecting the position of the slider and micro-actuator in relation to

the suspension arm. Additionally, silver ions or silver atoms in the silver paste may begin to migrate from the epoxy to the micro-actuator, affecting the performance of the micro-actuator. While other options for bonding the actuator to the suspension arm exist, such as gold ball bonding (GBB) and solder bump bonding (SBB), the rigidity of these options can lead to greater damage. In particular, the thinness of the piezoelectric transducer (PZT) surface layer of the micro-actuator can reduce the peel strength between the PZT layer and the bonding pad, causing the connection to crack and create an electrical short between the two. It is therefore desirable to support the micro-actuator and connect it to the suspension arm using a method that can create strong a connection without the risks of deformation.

5

#### Brief Description Of The Drawings

[0005] Figure 1 provides an illustration of a drive arm configured to read from and write to a magnetic hard disk as used in the art.

[0006] Figure 2 provides an illustration of a micro-actuator as used in the art.

[0007] Figure 3 describes a hard disk drive head gimbal assembly (HGA) with a 'U'-shaped micro-actuator according to an embodiment of the present invention.

[0008] Figure 4 provides an illustration of a U shape micro-actuator design according to an embodiment of the present invention.

[0009] Figure 5 provides an illustration of the configuration of the coating application according to an embodiment of the present invention.

[0010] Figure 6 provides an illustration of a step suspension according to an embodiment of the present invention.

[0011] Figure 7 provides an illustration of step actuator according to an embodiment of the present invention.

#### **Detailed Description**

5

10

15

20

25

30

[0012] A system and method for connecting an actuator to a suspension element is disclosed. The actuator is electrically coupled using a silver paste. The silver paste is further covered by a coating application to provide structural support. A step, attached to either the actuator base or the suspension tongue, provides further structural support and maintains a gap between the actuator and the suspension element.

[0013] Illustrated in an upside-down orientation, Figure 3 describes one embodiment of a hard disk drive head gimbal assembly (HGA) with a 'U'-shaped micro-actuator. In this embodiment, a slider 302 is bonded at two points 304 to a 'U'-shaped micro-actuator 306. In a further embodiment, the 'U'-shaped micro-actuator has a piezoelectric Lead Zirconate Titanate (PZT) beam (arm) 308 on each side of a ceramic support frame (actuator base) 310. The micro-actuator 306 is coupled to a suspension 312.

[0014] Figure 4 illustrates one embodiment of the 'U' shaped micro-actuator 306. A support frame 310 supports two piezoelectric Lead Zirconate Titanate (PZT) beams 308. In one embodiment, the support frame is ceramic. The 'U' shaped micro-actuator 306 is connected to the slider element 302. In one embodiment, the micro-actuator may be a piezoelectric micro-actuator, an electromagnetic micro-actuator, an electrostatic micro-actuator, a capacitive micro-actuator, a fluidic micro-actuator, or a thermal micro-actuator.

[0015] Figure 5 illustrates the coupling of the 'U' shaped micro-actuator 306 to the suspension element 312. In one embodiment, the 'U' shaped micro-actuator 306 is electrically coupled 502 to the suspension bonding pads 504 using a silver epoxy paste or resin. In a further embodiment, the slider 302 is electrically coupled 506 to the suspension bonding pads 508 using a silver epoxy paste or resin. In one embodiment, a coating application 510 covering the electric couplings for the micro-actuator 502 and the slider 506 provides physical support for these electric couplings. In particular, the coating application provides physical support for these electric couplings for the actuator element that can have movement independent of the movement of the HGA. In one embodiment, the coating application has a high glass transition temperature (Tg) (e.g., Tg > 120 degree Celsius), the temperature at which glassy solids transition to more flexible rubbery solids. In a further embodiment, the coating application has a high Young's modulus (E) (e.g., E >

0.6G Pa), the measure of the stiffness of a material. In one embodiment, the coating

application is an epoxy or a resin. The epoxy coating application can contain a filler material, such as metal, glass or a fiber material. The coating application protects the electric coupling from deformations caused by changes in humidity and temperature, as well as physical strain over time. The coating application can also prevent the migration of silver ions or atoms from the electric coupling into the electric layer of the PZT of the micro-actuator.

5

10

15

20

25

30

(

[0016] In a further embodiment of the present invention, a step configuration is implemented to further support the micro-actuator. The step configuration further reduces the amount of contact between the slider and the suspension during movement of the actuator. In one embodiment, the step configuration is implemented using a metal step 602 in the suspension tongue 312, as shown in **Figure 6**. In one embodiment, the step 602 is molded into the suspension tongue 312 at formation. In an alternate embodiment, a separate step piece 602 is coupled to the suspension tongue 312 before coupling the micro-actuator 306 to the suspension element 312. In one embodiment, the material for the step 602 is made of polyester, polyethylene, polymer, or ceramic. In a further embodiment, the step 602 is coupled to the suspension tongue 312 by epoxy, resin, anisotropic conductor film, or anisotropic conductive adhesive.

[0017] In one embodiment, the base of the micro-actuator 306 is thickened to create a step 702, as shown in Figure 7. The base step 702 of the micro-actuator 306 separates the micro-actuator 306 from the suspension 312 and maintains a parallel gap even during changes of temperature and humidity. In an alternate embodiment, the step 702 is created by attaching a separate step plate to the base of the micro-actuator 306. In one embodiment, the step configuration includes a first step element coupled to the micro-actuator and a second step element coupled to the suspension element. In an alternate embodiment, the step configuration includes a first step element created by thickening the base of the micro-actuator and a second step element is molded into the suspension tongue. In a further embodiment, the step 602 is coupled to the micro-actuator element 312 by epoxy, resin, anisotropic conductor film, or anisotropic conductive adhesive.

[0018] Although several embodiments are specifically illustrated and described herein, it will be appreciated that modifications and variations of the present invention are

covered by the above teachings and within the purview of the appended claims without departing from the spirit and intended scope of the invention.

#### What is claimed is:

5

20

- 1. An actuator, comprising: an actuator element physically supported by and coupled to a suspension element at at least one application site of a bonding agent, the bonding agent covered by a coating application
  - 2. The actuator of claim 1, wherein the actuator element is a micro-actuator.
- 3. The actuator of claim 2, wherein the micro-actuator is selected from a group consisting of a piezoelectric micro-actuator, an electromagnetic micro-actuator, an electrostatic micro-actuator, a capacitive micro-actuator, a fluidic micro-actuator, or a thermal micro-actuator.
  - 4. The actuator of claim 1, wherein the bonding agent is a silver paste.
- 15 5. The actuator of claim 1, wherein the coating application has a glass transition temperature greater than 120 degrees Celsius.
  - 6. The actuator of claim 1, wherein the coating application has a Young's modulus greater than 0.6G Pa.
  - 7. The actuator of claim 1, wherein the coating application is an epoxy agent.
  - 8. The actuator of claim 7, wherein the epoxy agent contains a filler ingredient.
- 9. The actuator of claim 8, wherein the filler ingredient is selected from a group consisting of metal, glass, or a fiber material.
  - 10. The actuator of claim 1, further comprising a step element to maintain a parallel spatial relationship between the actuator element and the suspension element.
  - 11. The actuator of claim 10, wherein the step element is created by thickening a portion of

the actuator element.

12. The actuator of claim 10, wherein the step element is coupled to a portion of the actuator element.

5

- 13. A system, comprising:
  - an actuator element;

a suspension element coupled to and supporting the actuator element by at least one application site of a bonding agent, the bonding agent covered by a coating application.

- 14. The system of claim 13, further comprising a magnetic head element coupled to the suspension element by at least one application site of a bonding agent, the bonding agent covered by a coating application.
- 15. The system of claim 13, wherein the actuator element is selected from a group consisting of a piezoelectric micro-actuator, an electromagnetic micro-actuator, an electrostatic micro-actuator, a capacitive micro-actuator, a fluidic micro-actuator, or a thermal micro-actuator.
- 20 16. The system of claim 15, wherein the micro-actuator is a piezoelectric micro-actuator.
  - 17. The system of claim 13, further comprising a slider element coupled to the actuator element.
- 25 18. The system of claim 13, further comprising a hard drive to be read by the slider element.
  - 19. The system of claim 13, wherein the bonding agent is a silver paste.
- 30 20. The system of claim 13, wherein the coating application has a glass transition temperature greater than 120 degrees Celsius.

- 21. The system of claim 13, wherein the coating application has a Young's modulus greater than 0.6G Pa.
- 22. The system of claim 13, wherein the coating application is an epoxy agent.

10

- 23. The system of claim 22, wherein the epoxy agent contains a filler ingredient.
- 24. The system of claim 23, wherein the filler ingredient is selected from a group consisting of metal, glass, or a fiber material.
- 25. The system of claim 13, further comprising a first step element to maintain a parallel spatial relationship between the actuator element and the suspension element.
- 26. The system of claim 25, wherein the first step element is created by thickening a portion of the actuator element.
  - 27. The system of claim 26, wherein a second step element is molded into the suspension element.
- 28. The system of claim 25, wherein the first step element is coupled to a portion of the actuator element.
  - 29. The system of claim 28, wherein a second step element is coupled to a portion of the suspension element.
  - 30. The system of claim 25, wherein the first step element is molded into the suspension element.
- 31. The system of claim 25, wherein the first step element is coupled to a portion of the suspension element.

- 32. The system of claim 25, wherein the first step element is coupled to a portion of the suspension element using one of a group of materials comprising epoxy, resin, anisotropic conductive film, and anisotropic conductive adhesive.
- 33. The system of claim 25, wherein the first step element is coupled to a portion of the micro-actuator element using one of a group of materials comprising epoxy, resin, anisotropic conductive film, and anisotropic conductive adhesive.
  - 34. A method, comprising:

20

coupling an actuator element to a suspension element using at least one application site of a bonding agent; and

covering the bonding agent with a coating application.

- 35. The method of claim 34, further comprising:
- 15 coupling a magnetic head element to the suspension element using at least one application site of the bonding agent; and

covering the bonding agent with the coating application.

- 36. The method of claim 34, wherein the actuator element is a micro-actuator.
- 37. The method of claim 36, wherein the micro-actuator is selected from a group consisting of a piezoelectric micro-actuator, an electromagnetic micro-actuator, an electrostatic micro-actuator, a capacitive micro-actuator, a fluidic micro-actuator, or a thermal micro-actuator.
- 25 38. The method of claim 34, wherein the bonding agent is a silver paste.
  - 39. The method of claim 34, wherein the coating application has a glass transition temperature greater than 120 degrees Celsius.
- 30 40. The method of claim 34, wherein the coating application has a Young's modulus greater than 0.6G Pa.

- 41. The method of claim 34, wherein the coating application is an epoxy agent.
- 42. The method of claim 41, wherein the epoxy agent contains a filler ingredient.
- 5 43. The method of claim 42, wherein the filler ingredient is selected from a group consisting of metal, glass, or a fiber material.
  - 44. The method of claim 34, further comprising maintaining a parallel spatial relationship between the actuator element and the suspension element using a first step element.
  - 45. The method of claim 44, further comprising creating the first step element by thickening a portion of the actuator element.

- 46. The method of claim 45, further comprising molding a second step element into the suspension element.
  - 47. The method of claim 44, further comprising coupling the first step element to a portion of the actuator element.
- 48. The method of claim 47, further comprising coupling a second step element to a portion of the suspension element.
  - 49. The method of claim 44, further comprising molding the first step element into the suspension element.
  - 50. The method of claim 44, further comprising coupling the first step element to a portion of the suspension element.
- 51. The method of claim 44, further comprising coupling the first step element to a portion of the suspension element using one of a group of materials comprising epoxy, resin, anisotropic conductive film, and anisotropic conductive adhesive.

52. The method of claim 44, further comprising coupling the first step element to a portion of the micro-actuator element using one of a group of materials comprising epoxy, resin, anisotropic conductive film, and anisotropic conductive adhesive.

## Abstract

5

A system and method for connecting an actuator to a suspension element is disclosed. The actuator is electrically coupled using a silver paste. The silver paste is further covered by a coating application to provide structural support. A step, attached to either the actuator base or the suspension tongue, provides further structural support and maintains a gap between the actuator and the suspension element.




FIG.1 Prior Art






FIG.2 Prior Art





F1G. 4

